

KORSCH Certified Pre-Owned XL 400 Tablet Press Serial Number K1500162

Certified Pre-Owned KORSCH XL 400 Tablet Press, manufactured in 2008 and fully refurbished in 2020. The XL 400 is a single-sided, high-speed rotary tablet press with single-layer and bi-layer capability.

Standard Features:

- ❑ Single Layer Execution
- ❑ 35-Station, TSM B Turret
- ❑ Exchangeable Turret Capability
- ❑ GMP Compression Zone
- ❑ Multi-Function Column (MFC)
- ❑ 100 kN Precompression Capability
- ❑ 100 kN Main Compression Capability
- ❑ Motorized Adjustment – Tablet Thickness
- ❑ Motorized Adjustment – Insertion Depth
- ❑ Motorized Adjustment – Dosing Cam
- ❑ Rotary, 3-Chamber Force Feeder
- ❑ Central Machine Control Diagnostic System
- ❑ Composite Cam Track Design
- ❑ Frequency Drive on Main Motor
- ❑ 3-Channel Discharge Chute
- ❑ 4-Zone Central Lubrication System
- ❑ Additional Lubrication Zone at Ejection Cam
- ❑ Full Set of Fill Cams (10 mm, 14 mm, 18 mm)
- ❑ Remote Stainless Steel Electrical Cabinet
- ❑ Fully Updated Control System
- ❑ Windows 10 Platform
- ❑ Allen-Bradley ControlLogix PLC Platform
- ❑ HMI Touch Screen
- ❑ Password Login
- ❑ Product Recipe
- ❑ Event Log
- ❑ Alarm and Alarm History
- ❑ Fully Compliant with 21 CFR Part 11



KORSCH
CERTIFIED PRE-OWNED

The Specialist.

KORSCH Certified Pre-Owned XL 400 Tablet Press **Serial Number K1500162**

Press Force Control:

- ❑ Display of Average Force - Precompression
- ❑ Display of Average Force - Main Compression
- ❑ Display of Single Forces by Punch Station - Precompression
- ❑ Display of Single Forces by Punch Station - Main Compression
- ❑ Feedback to Dosing Cam for Tablet Weight Control
- ❑ Display of Standard Deviation of Main Compression Force
- ❑ Entry of Press Force Limits - Precompression
- ❑ Entry of Press Force Limits - Main Compression
- ❑ Press Force Trending and Storage for Batch Report
- ❑ Full Functionality with Reduced Tools Configuration

Single Tablet Rejection:

- ❑ Rejects an Individual Tablet at All Press Speeds
- ❑ Records and Displays Punch Station as Tablets are Rejected
- ❑ Entry of Maximum Rejects from a Single Punch Station
- ❑ Entry of Maximum Rejects from All Punch Stations
- ❑ Reject Set-Up Parameters Stored in Product Recipe
- ❑ Reject Log Report

Documentation Package:

- ❑ Installation Qualification (IQ)
- ❑ Calibration Qualification (CQ)
- ❑ Operation Qualification (OQ)
- ❑ Operation and Service Manual
- ❑ Product Contact Parts Specification
- ❑ Lubrication Specification
- ❑ Spare Parts List
- ❑ Electrical Schematics
- ❑ Mechanical Assembly Drawings

KORSCH Certified Pre-Owned XL 400 Tablet Press Serial Number K1500162

Machine Specifications:

Punch Stations	35
Press Tools	B
Main Compression Force	100 kN
Precompression Force	100 kN
Maximum Tablet Diameter	16 mm
Press Speed	10-120 RPM
Output (Tabs/Hour) max.	252,000
Pitch Circle	410 mm
Maximum Tablet Thickness	8.5 mm
Net Weight	3,700 kg
Main Motor	18.5 KW
Main Power Supply	3 x 480 V, 60Hz

Warranty:

The Certified Pre-Owned KORSCH XL 400 is supported by a limited 6 month warranty.

For more information, please contact:

KORSCH America | sales@korschamerica.com | (508) 238-9080

